

LAC 720 SLF

TYPE | **12** ANS YEARS
GARANTIE - WARRANTY

FINITION WELDABLE PVDF
CLEANGARD SLF
Zgrzewalny obustronnie
PVDF lakier



720 g/m²



M2/B1/BS
NFPA701
B-S2-D0



3m



DICKSON
COATINGS

LAC 720 SLF

Nośnik <i>Support / Trägergewebe / Soporte / Supporto</i>	1100 dtex PES HT
Szerokość <i>Laize / Breite / Ancho / Altezza</i>	3.00 m
Powłoka <i>Enduction / Beschichtung / Revestimiento / Spalmatura</i>	PVC (Lowick)
Wykończenie <i>Fiinitio / Aussüstung / Acabado / Finizione</i>	Cleangard SLF
Ciężar całkowity <i>Poids Total / Gesamtgewicht / Peso total / Peso totale</i>	720g/m ²
Wytrzymałość na rozerwanie > NF EN ISO 1421 <i>Résistance rupture / Reissfestigkeit / Resistencia a la rotura / Resistenza alla rottura</i>	260/250 daN



77

Odbicie energii słonecznej (%)
Réflexion Solaire (%) / Wärme Reflection (%)
Reflexión Solar (%) / Riflessione Solare (%)



12

Pochłanianie energii słonecznej (%)
Absorption Soaire (%) / Wärme Absorption (%)
Absorción Solar (%) / Assorbimento Solare (%)

**Gtot
EXT**

0.08

Współczynnik słoneczny kombinacji tkaniny+ referencja szklenia C
Facteur solaire de l'ensemble toile + vitrage de référence C
Gesamtenergiedurchlassgrad der Kombination Verglasung C + Sonnenschutz
Factor solar de la combinacion del tejido + vidrio de referencia C
Fattore solare dell'insieme telo + vetro di riferimento C



**SYSTEM
LOWICK**

MADE IN
FRANCE



RESOURCE

**FINITION
CLEANGARD**

REACH
COMPLIANCE

vinyl plus
COMMITTED TO
SUSTAINABLE DEVELOPMENT

DICKSON
COATINGS



GLEN RAVEN